

Long Distance Shotgun Pickup with a Rich, Natural Tone Suitable for the camera mounting



The suspension handgrip is an optional accessory.

- 120mm long acoustic tube in a standard 250 mm length / 19mm diameter body, with the proprietary Sanken rectangular capsule for supersharp directivity. Thanks to the standard size, most of the existing accessories can be used.
- Greater directivity and extended reach over greater distances. A rich, natural sound makes the CS-2 ideal for a wide range of uses, such as for outdoor location sound, interviews, sports, drama, variety shows, and many more. Especially in the rich midrange, it can reproduce human voice very natural.
- This can be a long reach and high quality sound microphone by camera mounting.
- The light 110g weight of the CS-2 makes it ideal for camera mounting or boom pole operations.
- The "high boost switch" automatically compensates for the attenuation of high frequencies when the mic is used with a windscreen/windjammer for outdoor use. As a result, the full, natural sound is maintained.




Mounted on Canon XF305


<Specifications>

Directivity	; Super Cardioid / lobar	Output impedance (at 1kHz)	; 120Ω
Transducer	; DC biased condenser	Powering	; +48±4V phantom
Frequency range	; 50Hz - 20kHz	Current consumption	; less than 3.5mA
High boost switch	; +3dB / 8kHz	Weight	; 110g
Sensitivity (nominal at 1kHz)	; 63mV/Pa (-24dB,0dB=1V/Pa)	Dimensions	; 250mm X 19mm (diameter)
Equivalent noise level (A-weighted)	; 15dB-A	Surface finish	; matte black
Max SPL (1% THD)	; 130dB SPL	Connector	; XLR-3M
		Included accessory	; WM-23 urethane wind screen

<Frequency Response>



<Polar Pattern>



< Optional accessories >



WS-4 Cage windshield



WSJ-23 Softie windjammer



WJ-4 Windjammer for WS-4



WM-23 Urethane windscreen



GS-23 Suspension handgrip



TC-2 Flight case



< For camera mounting >

You need an extra rubber when you mount CS-2 with Canon and Sony cameras. →

For JVC camera, you need rings not a rubber. →



Specifications are subject to change without notice

SANKEN MICROPHONE CO., LTD.

2-8-8 Ogikubo, Suginamiku, Tokyo 167-0051 Japan

Phone: +81 3 3392 6581 FAX: +81 3 3393 2055 www.sanken-mic.com